

# WC e Accessori / Toilets and Accessories

## WC RM69 - Raske & Van Der Meyde - Holland



**Wc marino classico in porcellana** bianca, modello di semplicissimo utilizzo. Massima resistenza alla corrosione marina. Dimensioni d'ingombro: larghezza mm 440, profondità 420, altezza 350.

**Standard toilet.** Compact model with self-priming hand pump for below or above waterline installation. Will be supplied with standard or household type porcelain bowl and white plastic or wooden seat and cover. Simple installation. All parts are made of corrosion resistant materials. Dimensions: wide mm 440, width mm 420, height mm 350.

**Code # 31040** - coperchio in ABS / with plastic seat

**Code # 31041** - cop. legno bianco / with wooden seat

**3 Kg**



**Wc marino ultraleggero** con tazza in cicolac e coperchio in ABS. **Peso totale 3Kg.** Massima resistenza e semplicità nella manutenzione, costruito con materiali resistenti alla corrosione. Speciale attacco a baionetta della tazza per una più semplice manutenzione. Dimensioni d'ingombro: larghezza mm 440, profondità 420, altezza 350.

**Bayonet catch toilet, light weight:** approx 3 kilos, an excellent option where weight is an important factor. This light weight manual toilet has a self-priming hand pump for below or above waterline installation. The toilet is supplied with a ABS bowl which is fixed on the base by a bayonet catch. The bowl can easily be removed for maintenance or inspection. Besides that, this toilet is one of the light weighted on the market to-day. Will be supplied with white ABS seat and cover. All parts are made of corrosion resistant materials. Dimensions: wide mm 440, width mm 420, height mm 350.

**Code # 31050**



### Ricambi - Replacements

**Code # 31056** Base / Base

**Code # 31055** Pompa / Complete pump

**Code # 31060** Kit riparazione / Repair kit

**Code # 31045** Guarn. sottopompa / Outlet valve

**Code # 31046** Guarn. tazza / Bowl gasket



## WC Jabsco



**WC manuale Compact:** facili da usare e mantenere. Nuovo sistema di tenuta, maniglia ergonomica e leva di controllo del flusso opportunamente posizionate, potente azione turbina per un potente risciacquo, vaso in porcellana bianca, scarico con sezione di 38 mm, linee senza interstizi a forme arrotondate per una maggior igiene, pompa con montaggio invertibile per installazione destra o sinistra. Le toilet manuali possono ora essere aggiornate a funzionamento elettrico con l'utilizzo dell'apposito kit di conversione. Peso: 9,3 kg.

**Compact Manual WC.** Easy to clean white ceramic bowl, sturdy wood seat with durable baked enamel finish, forward angled pump for easy operation. Convenient top-mounted dry bowl selector, external seal housing/rod guide for easy replacement. Extra large seal housing allows piston rod assembly to be removed without removing valve cover. Smooth external surfaces with skirted base to maintain cleanliness, base of pump and valve cover are skirted to conceal gasket/flap valves. Triadic full-flow joker valve to avoid accidental blockage, multi-angle discharge port for versatility of plumbing connection. Corrosion resistant materials throughout for reliable fresh or salt water service. Weight : 9,3 kg.

**Code # 1400** - L450 x P485 x H335



### Ricambi per WC manuali / Replacements:

**Code # 1398** - Kit guarnizioni fino al 98 / Repair kit till 1998

**Code # 1401** - Kit guarnizioni dopo il 98 / Repair kit from 1998

**Code # 1402** - Pompa completa WC (senza base) / Pump

**Code # 1429** - Base / Base

### Kit elettrificazione:

conversione elettrica per wc manuali Jabsco. Si monta in pochi minuti al posto della pompa manuale.

Complete for 29090/2910 Series, compact and regular bowl, left or right hand manual toilets. Simple rotary control knob offers choice of "Flush and Discharge" or "Discharge Only". Existing discharge plumbing remains undisturbed for ease of installation. Miserly power consumption, typically less than the equivalent of 1.0 amp/hour each day. Vigorous 5 gpm (20 lpm) flush rate for rapid flushing, typically less than 10 seconds. Crevice free contours for added hygiene. Two powerful self-priming pumps for above or below waterline installation. Dual role design macerates waste for both overboard discharge and holdings tanks. Automatic inlet water checkvalve for additional security. Corrosion resistant materials throughout for reliable fresh or salt water service. Manual pump may be refitted to maintain service in the event of power failure. Retains existing joker valve to maintain automatic back-flow protection.

**Code # 1415** - 12V

**Code # 1416** - 24V

